

Specification Sheet

Part Number: 596-00246

SOLAR DISCONNECT

Solar Label, Reflective, SOLAR DISCONNECT, 6.5" x 1.0", VL, Red, 50/pkg

| Article Number | 596-00246 |
|---------------------|--|
| Туре | SOLARD |
| Color | Red (RD) |
| Features & Benefits | Made with UV stable inks and materials for durability and weather resistance Supplied with aggresive adhesive to ensure long life • Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections • Pre-printed labels offer significant time and cost savings over high priced engraved and lead time purchased markers |
| Quantity Per | roll |

| | International Fire Code (IFC 2012) as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed. |
|-----------------------|---|
| Short Description | Solar Label, Reflective, SOLAR DISCONNECT, 6.5" x 1.0", VL, Red, 50/pkg |
| Global Part Name | SOLARD-242/552-RD |
| Technical Description | Pre-Printed Solar Label, Reflective, "SOLAR DISCONNECT", 6.5" X 1", Red |
| Local Order Number 2 | Cross Reference = 10 per pack: 596-00674; Spanish version 50 per roll: 596-00810 |
| Width W (Imperial) | 6.5 |
| Width W (Metric) | 165.1 |
| Thickness T (Metric) | 64.0 |
| Height H (Imperial) | 1.0 |
| Height H (Metric) | 25.40 |
| | |
| Material | Type 242/552, UV Stable Reflective Vinyl w/Acrylic Laminate |

242/552

HellermannTyton pre-printed Solar Installation labels are designed to meet the requirements of the 2014 National Electrical Code (NEC 2014) and the 2012

Product Description

Material Shortcut

| Adhesive | Acrylic |
|---------------------------------|-----------------------------------|
| Halogen free | No |
| Adhesive Operating Temperature | -40°F to +302°F (-40°C to +150°C) |
| Operating Temperature (Metric) | -40°F to +174°F (-40°C to +79°C) |
| Reach Complaint(Article 33) | Yes |
| ROHS Complaint | Yes |
| Certification/Specification WEB | NEC2011 UL 969 IFC 2012 |
| Warranty (US) | Yes |
| UL Recognized (US) | Yes |
| | |
| Package Quantity(Imperial) | 50 |
| Package Quantity (Metric) | 50 |
| Customs Number | 3919905060 |
| Labels per Column | 1 |
| Labels per Row | 1 |
| Weight (Metric) | 0.521 |
| Weight (Imperial) | 3.2 |

