

RM Cores (6298370121)



Part Number: 6298370121

98 RM CORE SET

RM (Rectangular Modulus) cores allow better shielding than E type geometries while also providing easier winding accessibility and better power dissipation than a pot core configuration. Fair- Rite \square s standard RM cores all have a solid center post and standard height, low profile and alternate materials are available upon request.

 \square RM cores can be supplied with the center post gapped to a mechanical dimension or an A_L value.

Weight indicated is per pair or set.

Weight: 46 (g)

	<u> </u>				
Dim	mm	mm tol	nominal inch	inch misc.	
A	36.75	± 0.75	1.447		
В	12.25	± 0.15	0.482	_	
C	15.85	± 0.25	0.624	_	$\begin{array}{c} \begin{array}{c} \textbf{Chart Legend} \\ \hline \Sigma I/A : Core Constant, & l_e : Effective Path \\ \hline Length, & A_e : Effective Cross- Sectional Area, & V_e \\ \hline Effective Core Volume \\ \hline A_L : Inductance Factor \\ \end{array}$
D	8.55	± 0.20	0.337		
Е	25.45	± 0.55	1.002	_	
F	12.6	± 0.20	0.496	_	
G	13.4	min	0.528	min	
J	29.2	± 0.60	1.15		
& 4 =	materia	l grade.			Explanation of Part Numbers: Digits 1 & 2 = product class and

Electrical Properties				
$A_L(nH)$	$5500 \pm 25\%$			
Ae(cm ²)	1.41			
$\Sigma l/A(cm^{-1})$	4.3			
l _e (cm)	6.13			
$V_e(cm^3)$	8.675			
$A_{\min}(cm^2)$	1.247			

A_L value is measured at 1 kHz, B < 10 gauss.

888-324-7748

Fair- Rite Products Corp.

One Commercial Row, Wallkill, New York 12589-0288

845-895-2055

Fax: 845-895-2629

ferrites@fair- rite.com

www.fair- rite.com