



Prismatic Remote Sensing Target

3000X

Product Bulletin 3000X

August 2010

Description

3M™ Prismatic Remote Sensing Target 3000X is a micro-cube corner sheeting made of a flexible synthetic resin which will perform well with polarized light. The smooth, clear surface can be cleaned easily. 3000X sheeting has an aggressive pressure sensitive adhesive which provides an excellent bond to most clean, wax-free, dry, relatively non-porous, weather resistant surfaces. The adhesive is protected by a liner which is removed at the time of application and the reflector is pressed into position.

Product Features

- Specially designed micro-cube corner construction.
- Flexible synthetic resin construction.
- Pressure-sensitive acrylic adhesive backing.
- Impact resistant, low profile.

Product Advantages

- Maximum contrast per unit area.
- Typically 3,000 times brighter than a perfectly diffusing white surface.
- Can be hand or die-cut in shapes and sized to fit many applications.
- Easy to handle and apply to most clean surfaces.
- Can be used in high traffic zones with minimum surface obstruction.
- Readable at larger entrance angles (over 30° entrance).

Product Benefits

- Provides the desired signal at longer distances with polarized and laser controllers.
- Standard visible and infrared controllers can also be used.
- Allows greater system design flexibility per unit application.
- Saves time and reduces need for mechanical fasteners.
- Reduces cost and system downtime due to damaged reflectors.
- Improved signal with skewed containers or controllers.

Construction

<u>Product Number</u>	<u>Color</u>	<u>Lens</u>	<u>Liner</u>
3000X	White with linear pattern	Protected	Yes

Application

Remove oil, grease and/or dirt from the application surface through a solvent wipe with toluol, xylol, lacquer thinner, mineral spirits or VM&P naphtha. On lacquer surfaces, wipe with mineral spirits or heptane. After solvent wiping, dry the surface with a clean dry rag.

Cutting

The sheeting may be hand or die-cut, one sheet at a time or guillotined in stacks. Whenever two or more cut pieces are used, side by side, they must be matched to assure uniform brightness.

Typical Physical Properties

(Not recommended for specification purposes)

Retroreflective brightness varies with photo sensor geometry, retroreflector orientation and application. Performance in your application may be similar to the following typical values measured under standard conditions. Values stated in table are for measurements taken at observation angles of .1 or less.

Typical Luminance Factor*:	3000X
-4° reading:	3000X
Skewed 30° reading:	1500X
Applied Thickness:	.019"
Temperature Application Range:	50°F-100°F
*As compared to a diffuse white surface.	

Product Availability

2.54 cm x 22.86 m

5.08 cm x 22.86 m

7.62 cm x 22.86 m

Custom widths and lengths are available upon request.

Cleaning

Sheeting that requires cleaning after use should be flushed with water than washed with a mild detergent solution and soft bristle brush or sponge. Avoid pressure which may scratch the surface. Flush with water following washing. **Do not use solvents** to clean the sheeting surface.

Storage Conditions

3000x sheeting should be stored in a cool, dry area, preferably at 65-75°F (18-24°C) and 30-50% relative humidity, and should be applied within one year after purchase. Do not allow sheeting or finished applications to become wet in shipment or storage. If they become wet, immediately unpack and air dry.

Health and Safety Information

Read all health hazard, precautionary, and first aid statements found in the Material Safety Data Sheet and/or product label of chemicals prior to handling or use.

FOR INFORMATION OR ASSISTANCE

CALL:

1-800-553-1380

IN CANADA CALL:

1-800-265-1840

Internet:

www.3M.com/tss

3M assumes no responsibility for any injury, loss or damage arising out of the use of a product that is not of our manufacture. Where reference is made in literature to a commercially available product, made by another manufacturer, it shall be the user's responsibility to ascertain the precautionary measures for its use outlined by the manufacturer.

Important Notice

All statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed, and the following is made in lieu of all warranties, or conditions express or implied. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct, special or consequential, arising out of the use of or the inability to use the product. Before using, user shall determine the suitability of the product for his/her intended use, and user assumes all risk and liability whatsoever in connection therewith. Statements or recommendations not contained herein shall have no force or effect unless in an agreement signed by officers of seller and manufacturer.

3M is a trademark of 3M. Used under license in Canada.



Traffic Safety Systems Division

3M Center, Building 235-3A-09
St. Paul, MN 55144-1000
1-800-553-1380
www.3M.com/tss

3M Canada Company

P.O. Box 5757
London, Ontario N6A 4T1
1-800-3MHELPS

3M México, S.A. de C.V.

Av. Santa Fe No. 55
Col. Santa Fe, Del. Alvaro Obregón
México, D.F. 01210

Please recycle.

© 3M 2010. All rights reserved.
Bolger 10090143
Electronic Only